

Date : 21/07/2015 Page 1/11 Revision : N°7 (22/05/2015)

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SCHUTZLACK NGL 2002 ROSE Product code : SCH-NGL-2002R.

1.2. Relevant identified uses of the substance or mixture and uses advised against Lacquer protection for any surface

1.3. Details of the supplier of the safety data sheet

Registered company name : NGL CLEANING TECHNOLOGY SA. Address : Chemin de la Vuarpillière 7.CH-1260.NYON.SUISSE. Telephone : 00.41.(0).22.365.46.66. Fax : 00.41.(0).22.361.81.03. ngl@ngl-group.com www.ngl-group.com

1.4. Emergency telephone number : Urgence 145 24h/24h.

Association/Organisation : Centre Suisse Antipoison - Freiestrasse 16 - CH-8032 Zurich-.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



	\mathbf{V}	
GHS07	GHS02	
Signal Word :		
DANGER		
Product identifier EC 200-661-7	rs : PROPAN-2-OL	
Hazard statement	s :	
H222		Extremely flammable aerosol.
H229		Pressurised container: May burst if heated.
H319		Causes serious eye irritation.
H336		May cause drowsiness or dizziness.
Precautionary sta	tements - Prevention :	
P210		Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211		Do not spray on an open flame or other ignition source.



SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°1 (21/07/2015) NGL CLEANING TECHNOLOGY SA SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
Precautionary statements - Storage :	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P410 + P412	Protect from sunlight. Do no expose to temperatures exceeding 50 oC/122oF.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :
composition.

(EC) 1272/2008	Note	%
GHS02, GHS04	[1]	50 <= x % < 100
Dgr		
Flam. Gas 1, H220		
GHS07, GHS02	[1]	10 <= x % < 25
Dgr		
Flam. Liq. 2, H225		
Eye Irrit. 2, H319		
STOT SE 3, H336		
GHS02, GHS07	[1]	10 <= x % < 25
Dgr		
Flam. Liq. 2, H225		
Eye Irrit. 2, H319		
STOT SE 3, H336		
EUH:066		
GHS02	[1]	2.5 <= x % < 10
Dgr		
Flam. Liq. 2, H225		
	GHS02, GHS04 Dgr Flam. Gas 1, H220 GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066 GHS02 Dgr	GHS02, GHS04 [1] Dgr Flam. Gas 1, H220 GHS07, GHS02 [1] Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 GHS02, GHS07 [1] Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 GHS02, GHS07 [1] Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 GHS02 [1] GHS02 [1] Ogr [1]

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.



SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.



SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture.



SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

- European Onion (200	0/101/L0, 2000	15/LC, 2000/5/	$^{\prime\prime} \rm LC, 70/24/\rm LC)$,		
CAS	VME-mg/m3:	VME-ppm :	VLE-mg/m3:	VLE-ppm :	Notes :	
115-10-6	1920	1000	-	-	-	
67-64-1	1210	500	-	-	-	
- ACGIH TLV (Americ	can Conference of	of Governmental	Industrial Hygi	enists, Threshol	d Limit Values,	2010) :
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
67-63-0	200 ppm	400 ppm	-	-	-	
67-64-1	500 ppm	750 ppm	-	-	-	
64-17-5	1000 ppm	-	-	-	-	
- Germany - AGW (BA	uA - TRGS 900	, 21/06/2010) :				
CAS	VME :	VME :	Excess	Notes		
115-10-6	1000 ml/m3	1900 mg/m3	8(II)	DFG		
67-63-0	200 ml/m3	500 mg/m3	2(II)	DFG, Y		
67-64-1	500 ml/m3	1200 mg/m3	2(I)	DFG		
64-17-5	500 ml/m3	960 mg/m3	2(II)	DFG. Y		
- France (INRS - ED98	34 :2008) :					
CAS	VME-ppm :	VME-mg/m3:	VLE-ppm :	VLE-mg/m3:	Notes :	TMP No :
115-10-6	1000	1920	-	-	-	
67-63-0	-	-	400	980	-	84
67-64-1	500	1210	1000	2420	-	84
64-17-5	1000	1900	5000	9500	-	84
- UK / WEL (Workplac	e exposure limit	s, EH40/2005, 2	2007):			
CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :	
115-10-6	400 ppm	500 ppm	-	-	-	
67-63-0	400 ppm	500 ppm	-	-	-	
67-64-1	500 ppm	1500 ppm	-	-	-	
64-17-5	1000 ppm	-	-	-	-	

8.2. Exposure controls



Date : 21/07/2015 Page 6/11 Revision : N°7 (22/05/2015)

SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)



Date : 21/07/2015 Page 7/11 Revision : N°7 (22/05/2015)

SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES 9.1. Information on basic physical and chemical properties **General information :** Gas. Physical state : Spray. Color: N/A Odour: caracteristic Important health, safety and environmental information Not relevant. pH: Boiling point/boiling range : Not specified. Vapour pressure (50°C) : Not relevant. Density : Not stated. Insoluble. Water solubility : Melting point/melting range : Not specified. Self-ignition temperature : Not specified. Decomposition point/decomposition range : Not specified. % VOC : 97.10 Chemical combustion heat : Not specified. Inflammation time : Not specified. Deflagration density : Not specified. Inflammation distance : Not specified. Flame height : Not specified. Flame duration : Not specified. 9.2. Other information 971 VOC (g/l):

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

10.5. Incompatible materials

10.6. Hazardous decomposition products

- The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)



Date : 21/07/2015 Page 8/11 Revision : N°7 (22/05/2015)

SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances

Acute toxicity :

ETHANOL (CAS: 64-17-5)	
Oral route :	LD50 = 7060 mg/kg
	Species : Rat
Dermal route :	LD50 = 20000 mg/kg
	Species : Rabbit
T 1 1 4	
Inhalation route :	LC50 = 39 mg/l
	Species : Mouse
PROPAN A OL (CAR (7 (2 0))	
PROPAN-2-OL (CAS: 67-63-0)	
Oral route :	LD50 > 4700 mg/kg
	Species : Rat
Tub-lation much	LOSON AIDO LA INILAL QUANTIEIEDE ACMAIDO LA INILAL UNITE
Inhalation route :	LC50 % @IDC_LA_INHAL_QUANTIFIERS 46 % @IDC_LA_INHAL_UNITS

11.1.2. Mixture

No toxicological data available for the mixture.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

ETHANOL (CAS: 64-17-5) Fish toxicity :

Crustacean toxicity :

PROPAN-2-OL (CAS: 67-63-0) Fish toxicity : LC50 < 16000 mg/l Species : Oncorhynchus mykiss Duration of exposure : 96 h

EC50 > 10000 mg/l Species : Daphnia magna Duration of exposure : 48 h

LC50 > 9640 mg/l Species : Pimephales promelas Duration of exposure : 96 h

Crustacean toxicity :

EC50 > 2285 mg/l



Date : 21/07/2015 Page 9/11 Revision : N°7 (22/05/2015)

SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

Species : Daphnia magna Duration of exposure : 48 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

ETHANOL (CAS: 64-17-5) Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

PROPAN-2-OL (CAS: 67-63-0) Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

16 05 05 gases in pressure containers other than those mentioned in 16 05 04

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

14.1. UN number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable



SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°1 (21/07/2015) NGL CLEANING TECHNOLOGY SA SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

Date : 21/07/2015 Page 10/11 Revision : N°7 (22/05/2015)

A802

14.3. Transport hazard class(es)



14.4. Packing group

-

14.5. Environmental hazards

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	7	
	2.1	See SP63	-	SP277	F-D,S-U	63 190 277 327	E0	7	
						344 959			
				_					
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	203	75 kg	203	150 kg	A145	E0
								A167	
								A802	
	2.1	-	-	Y203	30 kg G	-	-	A145	E0
								A167	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/734/CEE modified by directive 2013/10/UE

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.
- Container information:
- No data available.
- Particular provisions :
- No data available.

15.2. Chemical safety assessment

No data available.



SCHUTZLACK NGL 2002 ROSE - SCH-NGL-2002R

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

0	
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.